

NOTES:

- 1-MATERIALS:
- -HELIX PLATE PER CSA G40.21 50W, MIN.FY=414 MPA, ULTIMATE STRENGTH 483 MPA
- -TUBE PER ASTM A500 GR C, FY=414 MPA, FU=483 MPA
- 2-ANY CHANGE OF MATERIAL IS SUBJECT TO GOLIATHTECH APPROVAL
- 3-WELD PERFORMED IN ACCORDANCE WITH CSA STANDARD W47.1 AND GOLIATHTECH WELDING PROCEDURES. WELDERS ARE ALSO CERTIFIED TO THE AWS STANDARD.
- 4-HOT-DIP GALVANIZED, PARTS PER ASTM A123.

3		
2		
1	INITIAL RELEASE	2023-07-18
REV	MODIFICATION	DATE

GOLIATH TECH

GOLIATHTECH PRESTIGE LINE

TITLE: 73 mm Helical Pile (6.4 mm wall), 279 mm Helix, 2134 mm Length

SEAL:	DWG. NO :
	GTPI27811-M
	DRAWN BY:
	ARG
	DESIGN BY:
	GOLIATHTECH
	CHECK BY:
	CPOC
	APP BY:
	CPOC
	OTHER NO:

FORMAT : A		REV.:	DATE :	PAGE :		
SCALE :	NTS	1	2024-01-24	1 DE		
THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND MAY NOT BE REPRODUCED OR COPIED						

WITHOUT THE EXPRESS WRITTEN PERMISSION OF A DULY AUTHORIZED REPRESENTATIVE OF

		Description	MECHANICAL ASD LOAD CAPACITY							
NC	Dimension		d Shaft ulm	Compression (kN)		Tension	Lateral	Bending	Max Soil Capacity	
	(mm)		Undraced straft, Liften	0 Coupler	1 Coupler	2 Coupler	(kN)	(kN)	Moment (N-m)	Comp/Ten* (kN)
Α	2,134		0	269	269	269				
В	279		2	125	67	36				
С	108		3	63	44	28	115	74	6,223	155
D	PITCH 76		5	33	27	20				
E	9.5		6	20	18	15				
F	25		Note: 1. Soil capacity	(P4) mus	st be dete	ermined p	er Section 4	.1.5 of this re	eport.	

- 2. Maximum ultimate soil capacity is determined from Pult = Kt x T based on the corresponding maximum installation torque rating for the specific pile model. Allowable soil capacity is determined from Pa = Pult /2.0 based on the corresponding maximum installation torque rating for the specific pile model. See Section 4.1.5 for additional information.
- 3. Mechanical torsion rating is the maximum torsional resistance of the steel shaft.
- 4. Maximum Torque Per Soil Tests is the maximum torque achieved during field axial verification testing that was conducted to verify the pile axial capacity related to pile-soil interaction.
- 5. Maximum Installation Torque rating is the lower of the "mechanical torsion rating" and the "maximum torque per soil tests".
- 6. The allowable soil capacity under the IRC must be determined in accordance with Equation 3 of Section 4.1.5 of this report, when applicable.
- *7. Min required installation depth for tension is 12D where D is the diameter of the uppermost
- 8. Max Soil Capacities based on the tube torsional cpacity.

Weld

38

73

14

G