

## NOTES:

1-MATERIALS:

1

- -HELIX PLATE PER CSA G40.21 50W, MIN.FY=414 MPA, ULTIMATE STRENGTH 483 MPA
- -TUBE PER ASTM A500 GR C, FY=414 MPA, FU=483 MPA
- 2-ANY CHANGE OF MATERIAL IS SUBJECT TO GOLIATHTECH APPROVAL 3-WELD PERFORMED IN ACCORDANCE WITH CSA STANDARD W47.1 AND GOLIATHTECH WELDING PROCEDURES. WELDERS ARE ALSO CERTIFIED TO THE AWS STANDARD.

3		·
2		
1	INITIAL RELEASE	2022-11-14
REV	MODIFICATION	DATE

## GOLIAŢHITECH

## **GOLIATHTECH VENTURA LINE**

TITLE: 48 mm Helical Pile (3.9 mm wall), 279 mm Helix, 2134 mm Length

SFAL:

DWG. NO:
VGTPI17811-M

DRAWN BY:
ARG

DESIGN BY:
GOLIATHTECH
CHECK BY:
CPOC

APP BY:
CPOC

OTHER NO:

FORMAT : A REV.: DATE : PAGE : SCALE : NTS 1 2024-01-22 1 DE 1

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND MAY NOT BE REPRODUCED OR COPIED WITHOUT THE EXPRESS WRITTEN PERMISSION OF A DULY AUTHORIZED REPRESENTATIVE OF GOLIATHTECH INC.

			WILCHANICAL ASD LOAD CAFACITY						
NO.	Dimension (mm)	Description	Undraged straft, LUIM	Compression (kN)	Tension (kN)	Lateral (kN)	Bending Moment (N-m)	Max Soil Capacity Comp/Ten* (kN)	
Α	2,134		0	91					
В	279		2	54					
С	108		3	16	54	21	1288	44	
D	PITCH 76		5	7					
Ε	9.5		6	4					
F	25		Note:	(D4) must be deter	mined per Sec	tion 4.1.5 of th	is report		
G	38		<ol> <li>Soil capacity (P4) must be determined per Section 4.1.5 of this report.</li> <li>Maximum ultimate soil capacity is determined from Pult = Kt x T based on the corresponding</li> </ol>						

2. Maximum ultimate soil capacity is determined from Pult = Kt x T based on the corresponding maximum installation torque rating for the specific pile model. Allowable soil capacity is determined from Pa = Pult /2.0 based on the corresponding maximum installation torque rating for the specific pile model. See Section 4.1.5 for additional information.

MECHANICAL ASD LOAD CAPACITY

- 3. Mechanical torsion rating is the maximum torsional resistance of the steel shaft.
- 4. Maximum Torque Per Soil Tests is the maximum torque achieved during field axial verification testing that was conducted to verify the pile axial capacity related to pile-soil interaction.
- 5. Maximum Installation Torque rating is the lower of the "mechanical torsion rating" and the "maximum torque per soil tests".
- 6. The allowable soil capacity under the IRC must be determined in accordance with Equation 3 of Section 4.1.5 of this report, when applicable.
- \*7. Min required installation depth for tension is 12D where D is the diameter of the uppermost helix.
- 8. Max Soil Capacities based on the tube torsional cpacity.

Weld

48

14

6