

## NOTES:

- 1-MATERIALS:
- -HELIX PLATE PER CSA G40.21 50W, MIN.FY=60 KSI, ULTIMATE STRENGTH 70 KSI
- -TUBE PER ASTM A500 GR C, FY=60KSI, FU=70KSI

1

2-ANY CHANGE OF MATERIAL IS SUBJECT TO GOLIATHTECH APPROVAL 3-WELD PERFORMED IN ACCORDANCE WITH CSA STANDARD W47.1 AND GOLIATHTECH WELDING PROCEDURES. WELDERS ARE ALSO CERTIFIED TO THE AWS STANDARD.

3		
2		
1	INITIAL RELEASE	2022-11-14
REV	MODIFICATION	DATE

## GOLIATHTECH

## **GOLIATHTECH VENTURA LINE**

TITLE: Screw Pile of 1 7/8 (0.154 wall) with a 11" Helix

SFAL:

DWG. NO: DRAWN BY: ARG DESIGN BY: **GOLIATHTECH** CHECK BY: CPOC APP BY: CPOC

OTHER NO:

FORMAT : A SCALE : NTS	REV.:	DATE: 2024-01-12	PAGE: 1 DE 1

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND MAY NOT BE REPRODUCED OR COPIED WITHOUT THE EXPRESS WRITTEN PERMISSION OF A DULY AUTHORIZED REPRESENTATIVE OF

		i	WEETIANICAL ASD LOAD CAI ACT I					
NO.	Dimension (inches)	Description	Judgeed Staft, Little	Compression (kips)	Tension (kips)	Lateral (kips)	Bending Moment (kips.ft)	Max Soil Capacity Comp/Ten * (kips)
Α	84		0	20.4				
В	11		5	12.2				
С	4 1/4		10	3.6	12.15	4.64	0.95	9.88
D	PITCH 3		15	1.6				
Ε	3/8		20	0.9				
F	1		Note:	· (D4)	i d O	# 4 4 F -£#	:	

1 1/2

1 7/8

9/16

Weld

1/4

- 1. Soil capacity (P4) must be determined per Section 4.1.5 of this report.
- 2. Maximum ultimate soil capacity is determined from Pult = Kt x T based on the corresponding maximum installation torque rating for the specific pile model. Allowable soil capacity is determined from Pa = Pult /2.0 based on the corresponding maximum installation torque rating for the specific pile model. See Section 4.1.5 for additional information.

MECHANICAL ASD LOAD CAPACITY

- 3. Mechanical torsion rating is the maximum torsional resistance of the steel shaft.
- 4. Maximum Torque Per Soil Tests is the maximum torque achieved during field axial verification testing that was conducted to verify the pile axial capacity related to pile-soil
- 5. Maximum Installation Torque rating is the lower of the "mechanical torsion rating" and the "maximum torque per soil tests".
- 6. The allowable soil capacity under the IRC must be determined in accordance with Equation 3 of Section 4.1.5 of this report, when applicable.
- \*7. Min required installation depth for tension is 12D where D is the diameter of the uppermost
- 8. Max Soil Capacities based on the tube torsional cpacity.