_		2										1						
В	A							ØB J J DETAIL A					NOTES : 1-MATERIALS: -HELIX PLATE PER CSA G40.21 50W, MIN.FY=414 MPA, ULTIMATE STRENGTH 483 MPA -TUBE PER ASTM A500 GR C, FY=414 MPA, FU=483 MPA 2-ANY CHANGE OF MATERIAL IS SUBJECT TO GOLIATHTECH APPROVA 3-WELD PERFORMED IN ACCORDANCE WITH CSA STANDARD W47.1 AND GOLIATHTECH WELDING PROCEDURES. WELDERS ARE ALSI CERTIFIED TO THE AWS STANDARD.			APPROVAL ) W47.1	В	
		Dimension (mm)	Description	MECHANICAL ASD LOAD CAPACITY								2						
	NO.			<i>et</i> ~ ~	Со	Compression		Tension (kN)	Lateral (kN)	Bending Moment (N-m)	Max Soil Capacity			RELEASE	2	023-07-18		
				ed sharulm	(kN)							REV	MODIF	ICATION	ION DATE			
				Unbraced shaft lum	0 Coupler	0 1 2 oupler Coupler Coup					Comp/Ten* (kN)		א ור	ŧŢΗ	TEC	н		
	Α	2,134		0	117	117	117							╹╉╹╹				
	В	330		2	43	23	14										4	
	C	108		3	3     19     14     10     52					2,047	70	GOLIATHTECH VENTURA LINE					-	
	D	PITCH 76		5	10	8	7					TITLE: 60 mm Helical Pile (3.9 mm wall), 330 mm Helix, 2134 mm       SF△I ·     DWG. NO :				4 mm Length	_	
	E	9.5		6	6	5	5					SEAL:			5. NO : TPI23813	-M		
	F	25		Note: 1. Soil capacity (P4) must be determined per Section 4.1.5 of this report.											WN BY:			
	G	38		2. Maximum ultimate soil capacity is determined from Pult = Kt x T based on the corresponding										AR	G GN BY:		-	
	Η	60		determined from Pa = Pult /2.0 based on the corresponding maximum installation torque rating GOLIATHTECH										1				
Α	I	14			for the specific pile model. See Section 4.1.5 for additional information.   CHECK BY:     3. Mechanical torsion rating is the maximum torsional resistance of the steel shaft.   CPOC										1,			
	J	6	Weld	A. Maximum Torque Per Soil Tests is the maximum torque achieved during field axial verification testing that was conducted to verify the pile axial capacity related to pile-soil interaction. CPOC											A			
				5. Maximum Installation Torque rating is the lower of the "mechanical torsion rating" and the "maximum torque per soil tests".   OTHER NO :     6. The allowable soil capacity under the IRC must be determined in accordance with Equation 3 of Section 4.1.5 of this report, when applicable.   FORMAT : A SCALE : NTS   DATE :   PAGE :   1 DE 1											1			
				helix without the express written permission											IATION AND MAY NOT BE REPRODUCED OR COPIED A DULY AUTHORIZED REPRESENTATIVE OF			
L				8. Max Soil Cap	8. Max Soil Capacities based on the the tube torsional cpacity.									GOLIATHTECH INC.				
-	2								1									