

IN	U	ı	ES	

1-MATERIALS:

-PLATE PER CSA G40.21 50W, MIN.FY=60 KSI, ULTIMATE STRENGTH 70 KSI

-TUBE PER ASTM A500 GR C, FY=60KSI, FU=70KSI

1

2-ANY CHANGE OF MATERIAL IS SUBJECT TO GOLIATHTECH APPROVAL 3-WELD PERFORMED IN ACCORDANCE WITH CSA STANDARD W47.1

AND GOLIATHTECH WELDING PROCEDURES. WELDERS ARE ALSO CERTIFIED TO THE AWS STANDARD.

 3
 2

 1
 INITIAL RELEASE 2023-08-04

 REV
 MODIFICATION DATE

GOLIAŢHITECH

GOLIATHTECH VENTURA LINE

TITLE: 10 Foot Screw Pile of 3 1/2 (0.250 wall) with a 09" Helix

SEAL:

DWG. NO:
VGTPI31209-10FT

DRAWN BY:
R.E

DESIGN BY:
GOLIATHTECH
CHECK BY:
CPOC
APP BY:
CPOC
OTHER NO:

FORMAT :	Α	REV.:	DATE :	PAGE :	
SCALE :	NTS	1	2023-08-04	1 DE	
THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND MAY NOT BE REPRODUCED OR COPIED					

THIS DUCLIMENT CUNTAINS PROPRIETARY INFORMATION AND MAY NOT BE REPRODUCED ON COPIES WITHOUT THE EXPRESS WRITTEN PERMISSION OF A DULY AUTHORIZED REPRESENTATIVE OF GOLIATHTECH INC.

	Dimension (inches)	Description	MECHANICAL ASD LOAD CAPACITY							
NO.			d Straft Light	Compression (kips)		Tension	Lateral	Bending	Max Soil Capacity	
			Undraged staft, Luften	0 Coupler	1 Coupler	2 Coupler	(kips)	(kips)	Moment (kips.ft)	Comp/Ten * (kips)
Α	120		0	48.8	48.8	48.8	22.79	18.50	6.20	43.75
В	9		5	34.5	22.3	13.9				
С	4 1/4		10	19.6	14.9	10.6				
D	PITCH 3		15	11.3	9.5	7.5				
Е	3/8		20	7.1	6.3	5.4				
F	1		Note:							

- 1. Soil capacity (P4) must be determined per Section 4.1.5 of this report.
- 2. Maximum ultimate soil capacity is determined from Pult = Kt x T based on the corresponding maximum installation torque rating for the specific pile model. Allowable soil capacity is determined from Pa = Pult /2.0 based on the corresponding maximum installation torque rating for the specific pile model. See Section 4.1.5 for additional information.

MECHANICAL ASD LOAD CAPACITY

- 3. Mechanical torsion rating is the maximum torsional resistance of the steel shaft.
- 4. Maximum Torque Per Soil Tests is the maximum torque achieved during field axial verification testing that was conducted to verify the pile axial capacity related to pile-soil interaction.
- Maximum Installation Torque rating is the lower of the "mechanical torsion rating" and the "maximum torque per soil tests".
- 6. The allowable soil capacity under the IRC must be determined in accordance with Equation 3 of Section 4.1.5 of this report, when applicable.
- *7. Min required installation depth for tension is 12D where D is the diameter of the uppermost helix.
- 8. Max Soil Capacities based on the tube torsional cpacity.

1 1/2

3 1/2

9/16

1/4

Weld

В