

## NOTES:

1-MATERIALS:

1

- -HELIX PLATE PER CSA G40.21 50W, MIN.FY=414 MPA, ULTIMATE STRENGTH 483 MPA
- -TUBE PER ASTM A500 GR C, FY=414 MPA, FU=483 MPA
- 2-ANY CHANGE OF MATERIAL IS SUBJECT TO GOLIATHTECH APPROVAL
- 3-WELD PERFORMED IN ACCORDANCE WITH CSA STANDARD W47.1
  AND GOLIATHTECH WELDING PROCEDURES. WELDERS ARE ALSO
  CERTIFIED TO THE AWS STANDARD.

3		
2		
1	INITIAL RELEASE	2023-07-18
REV	MODIFICATION	DATE

## GOLIAŢHITECH

## **GOLIATHTECH VENTURA LINE**

TITLE: 89 mm Helical Pile (6.4 mm wall), 229 mm Helix, 2134 mm Length

SEAL:

DWG. NO:
VGTPI31209-M

DRAWN BY:
ARG

DESIGN BY:
GOLIATHTECH

CHECK BY:
CPOC

APP BY:
CPOC

OTHER NO:

FORMAT : A	REV.:	DATE :	PAGE :	
SCALE: NTS	1	2024-01-24	1 DE	

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND MAY NOT BE REPRODUCED OR COPIED WITHOUT THE EXPRESS WRITTEN PERMISSION OF A DULY AUTHORIZED REPRESENTATIVE OF GOLIATHFECH INC.

		Dimension (mm)	Description	MECHANICAL ASD LOAD CAPACITY							
	NO.			d Shaft Julin	Compression (kN)		Tension	Lateral	Bending	Max Soil Capacity	
				Undraced straft, Life)	0 Coupler	1 Coupler	2 Coupler	(kN)	(kN)	Moment (N-m)	Comp/Ten* (kN)
I	Α	2,134		0	217	217	217			8,406	195
I	В	229		2	153	99	62				
I	С	108		3	87	66	47	101	82		
I	D	PITCH 76		5	50	42	33				
I	E	9.5		6	32	28	24				
١	F	25		Note:							
١	G	38		<ol> <li>Soil capacity (P4) must be determined per Section 4.1.5 of this rep</li> <li>Maximum ultimate soil capacity is determined from Pult = Kt x T t</li> </ol>						•	

2. Maximum ultimate soil capacity is determined from Pult = Kt x T based on the corresponding maximum installation torque rating for the specific pile model. Allowable soil capacity is determined from Pa = Pult /2.0 based on the corresponding maximum installation torque rating for the specific pile model. See Section 4.1.5 for additional information.

MECHANICAL ASD LOAD CAPACITY

- 3. Mechanical torsion rating is the maximum torsional resistance of the steel shaft.
- 4. Maximum Torque Per Soil Tests is the maximum torque achieved during field axial verification testing that was conducted to verify the pile axial capacity related to pile-soil interaction.
- 5. Maximum Installation Torque rating is the lower of the "mechanical torsion rating" and the "maximum torque per soil tests".
- 6. The allowable soil capacity under the IRC must be determined in accordance with Equation 3 of Section 4.1.5 of this report, when applicable.
- \*7. Min required installation depth for tension is 12D where D is the diameter of the uppermost helix.
- 8. Max Soil Capacities based on the tube torsional cpacity.

Weld

89

14