

## NOTES:

-PLATE PER CSA G40.21 50W, MIN.FY=60 KSI, ULTIMATE STRENGTH

-TUBE PER ASTM A500 GR C, FY=60KSI, FU=70KSI

1

2-ANY CHANGE OF MATERIAL IS SUBJECT TO GOLIATHTECH APPROVAL 3-WELD PERFORMED IN ACCORDANCE WITH CSA STANDARD W47.1 AND GOLIATHTECH WELDING PROCEDURES. WELDERS ARE ALSO

CERTIFIED TO THE AWS STANDARD.

3		
2		
1	INITIAL RELEASE	2023-08-04
REV	MODIFICATION	DATE

## GOLIATHTECH

## **GOLIATHTECH VENTURA LINE**

TITLE: 14 Foot Screw Pile of 3 1/2 (0.250 wall) with a 13" Helix

SFAL:

DWG. NO: VGTPI31213-14FT DRAWN BY: R.E DESIGN BY: **GOLIATHTECH** CHECK BY: CPOC APP BY: CPOC

OTHER NO:

FORMAT : A	ı	REV.:	DATE :		PAGE :
SCALE: N	TS	1	2023-0	8-04	1 DE 1

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND MAY NOT BE REPRODUCED OR COPIED WITHOUT THE EXPRESS WRITTEN PERMISSION OF A DULY AUTHORIZED REPRESENTATIVE OF GOLIATHTECH INC.

		Description	MECHANICAL ASD LOAD CAPACITY							
NO	Dimension (inches)		Unbraced Shaft Lites	Compression (kips)		Tension	Lateral	Bending	Max Soil Capacity	
	(inches)			0 Coupler	1 Coupler	2 Coupler	(kips)	(kips)	Moment (kips.ft)	Comp/Ten * (kips)
Α	168		0	58.4	58.4	58.4				
В	13		5	34.5	22.3	13.9				
С	4 1/4		10	19.6	14.9	10.6	22.79	18.50	6.20	43.75
D	PITCH 3		15	11.3	9.5	7.5				
Ε	3/8		20	7.1	6.3	5.4				
F	1		Note: 1. Soil capacity	(P4) mus	st be dete	rmined p	er Section 4	.1.5 of this r	eport.	

2. Maximum ultimate soil capacity is determined from Pult = Kt x T based on the corresponding maximum installation torque rating for the specific pile model. Allowable soil capacity is determined from Pa = Pult /2.0 based on the corresponding maximum installation torque rating for the specific pile model. See Section 4.1.5 for additional information.

MECHANICAL ACDIOAD CADACITY

3. Mechanical torsion rating is the maximum torsional resistance of the steel shaft.

4. Maximum Torque Per Soil Tests is the maximum torque achieved during field axial verification testing that was conducted to verify the pile axial capacity related to pile-soil interaction.

- 5. Maximum Installation Torque rating is the lower of the "mechanical torsion rating" and the "maximum torque per soil tests".
- 6. The allowable soil capacity under the IRC must be determined in accordance with Equation 3 of Section 4.1.5 of this report, when applicable.
- \*7. Min required installation depth for tension is 12D where D is the diameter of the uppermost
- 8. Max Soil Capacities based on the tube torsional cpacity.

1 1/2

3 1/2

9/16

1/4

Weld