

## NOTES:

1-MATERIALS:

-HELIX PLATE PER CSA G40.21 50W, MIN.FY=414 MPA, ULTIMATE STRENGTH 483 MPA

-TUBE PER ASTM A500 GR C, FY=414 MPA, FU=483 MPA

2-ANY CHANGE OF MATERIAL IS SUBJECT TO GOLIATHTECH APPROVAL 3-WELD PERFORMED IN ACCORDANCE WITH CSA STANDARD W47.1 AND GOLIATHTECH WELDING PROCEDURES. WELDERS ARE ALSO

CERTIFIED TO THE AWS STANDARD.

1

3		
2		
1	INITIAL RELEASE	2023-07-18
REV	MODIFICATION	DATE

## GOLIAŢHITECH

## **GOLIATHTECH VENTURA LINE**

TITLE: 89 mm Helical Pile (6.4 mm wall), 330 mm Helix, 2134 mm Length

SEAL:

DWG. NO:
VGTPI31213-M

DRAWN BY:
ARG

DESIGN BY:
GOLIATHTECH
CHECK BY:
CPOC

APP BY:
CPOC

OTHER NO:

FORMAT : A SCALE : NTS REV.: DATE : PAGE : 1 DE 1

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND MAY NOT BE REPRODUCED OR COPIED WITHOUT THE EXPRESS WRITTEN PERMISSION OF A DULY AUTHORIZED REPRESENTATIVE OF GOLIATHTECH INC.

		Description	MECHANICAL ASD LOAD CAPACITY							
NO.	Dimension (mm)		Shaft	Compression (kN)			Tension	Lateral	Bending	Max Soil Capacity
			Unbraced shaft, Liter	0 Coupler	1 Coupler	2 Coupler	(kN)	(kN)	Moment (N-m)	Comp/Ten* (kN)
Α	2,134		0	260	260	260				
В	330		2	153	99	62				
С	108		3	87	66	47	101	82	8,406	195
D	PITCH 76		5	50	42	33				
Ε	9.5		6	32	28	24				
F	25		Note:	(D4) mus	at he dete	rminad n	or Coation 4	1 E of this r	oport	

- 1. Soil capacity (P4) must be determined per Section 4.1.5 of this report.
- 2. Maximum ultimate soil capacity is determined from Pult = Kt x T based on the corresponding maximum installation torque rating for the specific pile model. Allowable soil capacity is determined from Pa = Pult /2.0 based on the corresponding maximum installation torque rating for the specific pile model. See Section 4.1.5 for additional information.

MATCHANICAL ACD LOAD CADACITY

- 3. Mechanical torsion rating is the maximum torsional resistance of the steel shaft.
- 4. Maximum Torque Per Soil Tests is the maximum torque achieved during field axial verification testing that was conducted to verify the pile axial capacity related to pile-soil interaction.
- 5. Maximum Installation Torque rating is the lower of the "mechanical torsion rating" and the "maximum torque per soil tests".
- 6. The allowable soil capacity under the IRC must be determined in accordance with Equation 3 of Section 4.1.5 of this report, when applicable.
- \*7. Min required installation depth for tension is 12D where D is the diameter of the uppermost helix.
- 8. Max Soil Capacities based on the the tube torsional cpacity.

Weld

G

38

89

14

6